




Product Specification





<p>RED 14-4</p>		<p>Cross Section</p>	<p>Packaging</p>
<p>Spec No: S-044 Date: 06/01/2016</p>			<p> Box 500 Ft.</p> <p>Colors</p> <p><input type="checkbox"/></p>

<h2>Description</h2>									
<p>RED Atom 14-4, 14AWG, 4 Conductor, Stranded, Bare Copper, CL3, CM, & FT4 Rated for Audio Applications.</p>									
<p>Description</p> <table border="0"> <tr> <td>Rated Voltage (V)</td> <td>300</td> </tr> <tr> <td>Rated Temperature (°C)</td> <td>75</td> </tr> <tr> <td>Product Standard Certification</td> <td>ETL CL3 or cETL CM</td> </tr> <tr> <td>Flame test</td> <td>FT4</td> </tr> </table>		Rated Voltage (V)	300	Rated Temperature (°C)	75	Product Standard Certification	ETL CL3 or cETL CM	Flame test	FT4
Rated Voltage (V)	300								
Rated Temperature (°C)	75								
Product Standard Certification	ETL CL3 or cETL CM								
Flame test	FT4								
<p>Application</p> <p>Power-limited circuit cables for use as fixed wiring within buildings principally for Class 3 and Class 2 circuits.</p>									
<p>Reference Standard:</p> <p>UL 13 & 444</p>									

<h2>Performance</h2>											
<p>Electrical Characteristics (20°C)</p> <table border="0"> <tr> <td>Voltage</td> <td>300 Volts RMS</td> </tr> <tr> <td>Spark Test</td> <td>2500V DC</td> </tr> <tr> <td>Temperature</td> <td>-20°C to 75°C</td> </tr> <tr> <td>Insulation Resistance (Ω/KM)</td> <td>≥ 200M Ω/KM</td> </tr> <tr> <td>Dielectric Strength</td> <td>1500V AC for 2 s</td> </tr> </table>		Voltage	300 Volts RMS	Spark Test	2500V DC	Temperature	-20°C to 75°C	Insulation Resistance (Ω/KM)	≥ 200M Ω/KM	Dielectric Strength	1500V AC for 2 s
Voltage	300 Volts RMS										
Spark Test	2500V DC										
Temperature	-20°C to 75°C										
Insulation Resistance (Ω/KM)	≥ 200M Ω/KM										
Dielectric Strength	1500V AC for 2 s										
<p>Mechanical Characteristics</p> <table border="0"> <tr> <td>Test Object</td> <td>Jacket</td> </tr> <tr> <td>Test Material</td> <td>PVC</td> </tr> <tr> <td>Jacket Tensile Strength</td> <td>≥13.8MPa</td> </tr> </table> <p><small>Sequential footmarks applied every four feet in conjunction with the print legend. "XXX/XXX" Stands for Length. eg: 000/1000; 004/0996; 008/0992...</small></p>		Test Object	Jacket	Test Material	PVC	Jacket Tensile Strength	≥13.8MPa				
Test Object	Jacket										
Test Material	PVC										
Jacket Tensile Strength	≥13.8MPa										

<h2>Construction</h2>									
<p>Conductor Component</p> <p>AWG</p> <p>Construction (± 0.008mm)</p> <p>Insulation</p> <p>Nom. Thickness (mm)</p> <p>Insulation Dia. (±0.2mm)</p>	<p>Stranded Bare Copper</p> <p>4C</p> <p>14</p> <p>19/0.37</p> <p>PVC</p> <p>0.40</p> <p>2.7</p>								
<p>Ripcord Jacket</p> <p>Nom. Thickness (± 0.15mm)</p> <p>Outer Dia. (±0.3mm)</p>	<p>150D Nylon Thread</p> <p>PVC</p> <p>0.55</p> <p>7.4</p>								
<p>Insulation/Conductor Colors</p> <table border="0"> <tr> <td>Component</td> <td>1. Red</td> </tr> <tr> <td></td> <td>2. Black</td> </tr> <tr> <td></td> <td>3. White</td> </tr> <tr> <td></td> <td>4. Green</td> </tr> </table>		Component	1. Red		2. Black		3. White		4. Green
Component	1. Red								
	2. Black								
	3. White								
	4. Green								
<p>Jacket Colors</p>	<p>Pantone White</p>								

<h2>Compliance</h2>			
		<p>CL3</p>	<p>FT4</p>

Jacket Marking (Black)

RED Atom 14-4 SPEAKER CABLE 14AWG 4C ETL LISTED 5002121 (ETL) CL3 OR c(ETL) CM FT4 75C ROOM: ENT KIT NK FAM LR DR POWD OFF POO PAT MBR MBA BR1 BR2 BR3 BR4 BR5 GAR GYM 1 2 3 4 5 6 "ROHS" XXX/XXX FT